

hyCLEANER®

www.hyCLEANER.eu

hyCLEANER® red EVO III

- The **hyCLEANER® red EVO III** cleans different forms of façades, surfaces and materials - especially horizontal profiled metal cladding - very gently, effective, fast and above all, economic. The machine works with high-pressure water and does not need any electrical connection. Both, the glass and the frames are cleaned simultaneously. All water leading elements are made out of stainless steel. Purified-water can be used and the glass surfaces dry up, leaving no streaks behind.
- A further advantage of **hyCLEANER® red EVO III** is the running wheels. They do not leave any marks on the surface of the façade - gentle cleaning can be so easy!
- Mounting of **hyCLEANER® red EVO III** can be done on nearly any lifting device - especially working platforms such as scissor lifts, boom lifts and small truck-mounted platforms.

Technical data

Machine

Brush width	approx. 800 mm
Brush diameter	approx. 400 mm
Balance of movement	max. 500 mm
Running wheel Ø big	500 mm
Total weight	≤ 65 kg
Traffic load	min. 20 kp/m ² (197 N/m ²) max. 82 kp/m ² (807 N/m ²)

Motor

Water pressure	min. 120 bar max. 160 bar
Water quantity	min. 9 l/Min max. 12 l/Min
Revolutions regulated via water quantity	yes max. 400 rpm
Performance*	max. 9 m ² /min
*depending on degree of soiling	

Alterations in construction reserved / 08.01.2015

TG hyLIFT®

TG hyLIFT® GmbH
Maybachstraße 6
D-48599 Gronau
phone +49 2562 99254 0
fax +49 2562 99254 10
info@tg-hylift.com
www.tg-hylift.com
www.hyCLEANER.eu